

# SWA401

Wall Mount Powered Speakers



#### IN WALL CONTROL

Two 3.5mm stereo inputs, a 'dual-function' USB socket (charging and audio playback) plus volume control.

# SWA401

## Wall-Mount Loudspeakers, Amplifier & In-Wall Control System

40W

40w speaker output



Built in amplifier



Great sound from compact speakers



In-Wall & Remote Control



The SWA401 is a high efficiency, high output power audio solution that features an In-Wall amplifier and control surface, and is the perfect complement to interactive whiteboards or interactive flat panels.

The SWA401 is ideally suited to the education and corporate environments where high definition audio is a must-have; or where audio is poor and needs to be improved in a cost-effective way. It features two 3.5mm stereo inputs and a USB socket that has two functions; it can be used as a USB 5v charging output (for mobile, tablet and other portable devices), or for audio playback from flash drive - controlled from the remote control. Three year warranty as standard.

Three Digital Signal Processing (DSP) settings allows for exceptional audio reproduction making it versatile enough to use in small to large classrooms, meeting rooms and large halls.

**Conxeasy**<sup>™</sup>

Premier Group (UK) Ltd - Exclusive provider of ConXeasY™ Audio Products

# SWA401

Wall Mount Powered Speakers

# ConXeasy™ SWA401

## Wall-Mount Loudspeakers, Amplifier & In-Wall Control System

The SWA401 is a high efficiency, high output power audio solution that is the perfect complement to interactive whiteboards or interactive flat panels. The SWA401 was developed based on the needs and feedback of customers looking for a cost-effective audio solution that featured In-Wall Control Surface (IWCS) flexibility, performance and high-quality sound.



### Specifications

#### INPUTS (On In Wall Control System)

2x 3.5mm stereo mini-jacks : 20k ohms  
USB: Playback of MP3/WMA/WAV files

#### OUTPUTS

USB: 5v charging of devices (Smartphone, Tablet etc.)

#### AMPLIFIERS

Continuous Average Output Power: 40W (20W x 2)  
Both channels: 1kHz / 1% THD  
Rated Distortion (1/2 power): 0.40%  
Rated Impedance: 4 ohms  
Frequency Response (50-20kHz): ±2 dB

#### SPEAKERS

Mid-High Range : 1.5" Neodvminu x 1  
Bass: 4" Ferrite driver x1

#### PERFORMANCE

Output power (RMS @ THD<40%) : 40W  
Frequency response : 50 Hz - 25K Hz ±2 dB  
Dynamic Signal Processing : Speech / Hall / Music

#### CONTROL

In Wall Control System: Vol+ / Vol- / Source / Mode / Power  
Remote Control keys : ON/OFF, MUTE, VOL+, VOL-, INPUT, SPEECH, HALL, MUSIC

#### AC POWER

External 19Volt DC Power Supply  
Power Requirements: AC 230 - 240V ~ 50Hz

#### DIMENSIONS

Speakers (each): 160 x 150 x 240 mm (W, D, H)  
In Wall Control System (each): 50 x 29 x 50 mm (W, D, H)

#### WHAT'S IN THE BOX

1x Pair Loudspeakers with Integral Wall Brackets  
1x Amplifier/IWCS  
1x Power Supply  
1x Remote Control

Premier

+44 (0) 1633 895918  
info@steljesaudio.co.uk  
www.conxeasy.com

©Premier Group (UK) Ltd. Details are subject to change without notice. ConXeasy™ is a brand of Premier Group (UK) Ltd in the U.K. and/or other countries.  
All other logos and trademarks acknowledged. E&OE.

conxeasy™