




# Pair 54w Active Loudspeakers

SP-900P EU SAP: 4820817

[vav.link/sp-900p](http://vav.link/sp-900p)

Built-in 2 x 27-watt digital amplifier  
Two summed inputs (1 x Minijack / 1 x 2-Phono)  
Internal Power Supply  
Adjustable wall brackets included

The SP-900P are Vision's most cost-effective audio solution. They are purpose-built for small meeting rooms and classrooms. Incredible value for money; they offer great sound quality and Vision's trademark ease of installation. Perfect for meeting spaces.



## 2-Way

A 5.25" woofer is complemented by a Mylar dome tweeter. The dome tweeter offers a wide dispersion so everyone in the room can hear at the same volume. This means loud and clear sound for meeting rooms and classrooms.

## Volume Control

The volume dial is on the rear of the 'master' loudspeaker – the one containing the amplifier. It is alongside the hard power switch.

## Wall Brackets

The brackets allow installers to easily tilt side to side, and the use of a dome tweeter means the speakers can be mounted on their sides allowing downward tilt. Alternately, leave the brackets off and use as shelf speakers.

## Multiple Inputs

The rear panel of the master loudspeaker offers minijack and 2-phono (RCA) inputs.

## ABS Chassis

Heavy-weight plastic material is used for the chassis, allowing a rigid acoustic chamber for distortion-free sound.

## Bass Reflex

A bass reflex port allows greater excursion of the woofer, allowing the woofer to produce lower frequencies, and the phase-delayed movement of air from behind the woofer to the front reinforces the bass even more.

## Inputs Summed

The inputs are combined at input stage meaning there is no input selection switch. *Note: when both inputs are connected all source and display devices in the system should be powered from the same mains power source, otherwise earth hums will occur.*



VISION

MANUAL

Quick manual

EN PDF 87.59 KB

[files.visionaudiovisual.com/products/SP-900P/certificates/SP-900P\\_RCM\\_search.pdf](files.visionaudiovisual.com/products/SP-900P/certificates/SP-900P_RCM_search.pdf)

Manual

EN PDF 761.36 KB

[files.visionaudiovisual.com/products/SP-900P/manuals/SP-900P\\_manual.pdf](files.visionaudiovisual.com/products/SP-900P/manuals/SP-900P_manual.pdf)

IMAGE

Product Images

ZIP 14.65 MB

<files.visionaudiovisual.com/products/SP-900P/images/SP-900P.zip>

Menu

PNG 1.05 MB

[files.visionaudiovisual.com/products/SP-900P/images/SP-900P\\_menu.png](files.visionaudiovisual.com/products/SP-900P/images/SP-900P_menu.png)

Product Images

PNG 5.15 MB

<files.visionaudiovisual.com/products/SP-900P/images/SP-900P.png>

Freq

PNG 102.29 KB

[files.visionaudiovisual.com/products/SP-900P/images/SP-900P\\_freq.png](files.visionaudiovisual.com/products/SP-900P/images/SP-900P_freq.png)

Front

PNG 4.70 MB

[files.visionaudiovisual.com/products/SP-900P/images/SP-900P\\_front.png](files.visionaudiovisual.com/products/SP-900P/images/SP-900P_front.png)

Rear

PNG 2.52 MB

[files.visionaudiovisual.com/products/SP-900P/images/SP-900P\\_rear.png](files.visionaudiovisual.com/products/SP-900P/images/SP-900P_rear.png)

Rear angle

PNG 2.22 MB

[files.visionaudiovisual.com/products/SP-900P/images/SP-900P\\_rear\\_angle.png](files.visionaudiovisual.com/products/SP-900P/images/SP-900P_rear_angle.png)

SPECIFICATIONS

PRODUCT DIMENSIONS

245 x 183 x 164 mm / 9.6" x 7.2" x 6.5" (tall x wide x deep for each speaker)

PACKAGED DIMENSIONS

395 x 235 x 275 mm / 15.5" x 9.2" x 10.8"

PRODUCT WEIGHT

Master: 2.7 kg / 5.9 lb Slave: 2.5 kg / 5.6 lb

PACKAGED WEIGHT

5.5 kg / 12.2 lb

CONSTRUCTION MATERIAL

PP

COLOUR

White

WOOFER

5.25" Paper

TWEETER

0.5" Mylar Dome

INPUTS

Minijack (3.5mm) 2-Phono (RCA) (Summed)

SPEAKER OUTPUT

Removable Phoenix type

SPEAKER INPUT (ON SLAVE)

Bare Wire Screw type

LOW IMPEDANCE DYNAMIC POWER

2 x 27 watt at 8 ohms

LOW IMPEDANCE RMS POWER

2 x 15 watt at 8 ohms

SENSITIVITY

101 dB (1w/1m)

FREQUENCY RESPONSE

50Hz-20kHz

ACCESSORIES INCLUDED

2 x Wall brackets 1 x Speaker Cable 5m (16.4 ft) 1 x Euro Figure-8 Power cable 1.8 m (6 ft) long 1 x UK Figure-8 Power cable 1.8 m (6 ft) long 1 x AU Figure-8 Power cable 1.8 m (6 ft) long 1 x US Figure-8 Power cable 1.8 m (6 ft) long Note: no input cables included

POWER SUPPLY

100-240v 50/60Hz AC Internal Power Supply

WARRANTY

Lifetime return-to-base

COMPLIANCE

RoHS, WEEE, CE/EMC, FCC, RCM-POC, RCM-SDOC

ORDER PART CODE

SP-900P [EU SAP: 4820817 / US SAP: tba]

TOTAL HARMONIC DISTORTION (THD)

1%