IFD55TH652/3





55" Android Based Interactive Flat Panel Displays

Key Features



Palm Erase

Automatic palm erasing function allows teachers and students to simplify the white board experience with smooth writing and erasing.



Ease of use with Android

Android gives teachers one touch access for lessons and collaboration tools including whiteboard, web browser, apps library, and native wireless screen sharing.





Wireless Presentation

Teachers, students or any user can share their screen efficiently and conveniently in the classroom or meeting room via EShare application. This application can connect any operating system and show up to 4 different screen at the same time.

Different Sizes for various classrooms

Available in a variety of large screen sizes, the IFD range gives customers the options to choose exactly what they need for their room size.



Crestron Connected

Crestron Connected certification complements VESTELs presence with inside the corporate, retail, government, better training and hospitality markets, all of which use expert AV controls. As those sectors hold to evolve with growing necessities for simple-to-use merchandise, seamless integration, dependable answers and community connectivity.

IFD55TH652/3



DISPLAY

Screen Size Panel Technology Backlight Type Brightness (typical) Native Resolution Contrast Ratio (typical) Dynamic Constrast Ratio Panel Life Time (Min.) Response Time (typical) Active Area (H x V) Viewing Angle Color Value Screen Treatment Haze Level Refresh Rate Front Type Orientation Operation Hours Area of Usage

55" IPS Direct-Type LED 400 cd/m² UHD: 3840 x 2160 - HDR10 1300:1 40000:1 30000 Hr 6 ms 1210 x 681 mm 178° Vert., 178° Hor. (89U/89D/89L/89R) @ CR>10 16.7 M (8-bit) 2H 8% 60 Hz Black Super Narrow Bezel Horizontal 16/7 Indoor

REAR I/OS

RGB Input RGB Output Video Input Video Output Audio Input Audio Output External Control External Sensor VGA(DE-15F) N/A 3xHDMI2.0, 2xUSB2.0, USB2.0(Internal), 1xMicroSD HDMI2.0 Line In L/R Headphone, Optic SPDIF RS232(DE-9F), 2*Ethernet(RJ45), Service(RJ12) RJ12

MECHANICAL

Product Dimensions (WxDxH) Package Dimensions (WxDxH) Product Weight Package Weight Vesa Mounting Bezel Width 1280 x 123 x 751 mm 1480 x 265 x 930 mm 29.45 kg 38.15 kg 400 x 200 mm B:34 | T:34 | L/R:34 mm

POWER

Power Supply

90% 110 VAC - 240 VAC

FEATURES

Main Features	USB-Autoplay, Auto-switch on Failover, Control Button Lock, HDMI Wake-Up
Mechanical Features	IR Touch, Joystick, IR Extender Support, Rocker Switch, Detachable power cable, Carrying handles, Detachable logo positioning, Cable Holders
Optional Features	OPS Compliance
Speaker	2 x 8 W

CERTIFICATION

Safety	YES
EMC	YES
CE	YES
Reability Approval	YES

BUILT-IN SYSTEM

Mainboard Model

17MB135VS

TOUCH INTERACTIVITY

Type of Touch Technology Continuous Touch Points Sensitivity Connectivity Compatibility Orientation Calibration Accuracy Reporting Rate Glass Type

Frame Rate

Communication

Supply Voltage

Average Current

Response Time

Touch Accuracy

Touch Durability

HID Compatibility

Object Sizes for Touch

Power Supply Mode

Infrared (IR) Technology 10 Points Any touch with finger, gloved hand or pointer HID, TUIO, Flash Windows[®]7, Windows[®]8, Windows[®]10, Vista, XP, Mac[®] OS, Linux, Android Landscape support No need %90 < Up to 450 fps Anti Glared (AG), 4mm Tempered up to 450 fps USB 2.0 USB DC 5V +/- 5% <400mA <10ms +/-2mm (over 90% area) Unlimited Yes USB 5mm

ENVIRONMENTAL CONDITIONS

Operating Temperature Operating Humidity +40°C / 0°C 90%

POWER CONSUMPTION

83 W ≼0.5W

ACCESSORY

Standard

Typical

Deep Standby

QSG, IB, Power Cord, Remote Control, RC Battery, Mounting Kit, Extension Brackets, IR Extender Cable

		1	
MODEL	DIMENSIONS (mm)	1910	
MODEL 55495 IFPD	DIMENSIONS (mm)		TILLEBWARES & NAME: 55495 IFPD REV
	WIDTH DEPTH HEIGHT		TILLERWARDS K NAME: 55495 IFPD REV. 100/0000 4000 DEXEMPLANE (DTTQ) DATE DESCRIPTION (DTTQ)