
# F80-Q7

## 7,000 lumens, WQXGA, DLP laser phosphor projector





- Stunning images with superb color performance
- Ultimate installation flexibility, 24/7 operation
- 3D capable

The stunning image quality and laser phosphor light source of Barco's F80 projectors enable you to provide exceptional experiences while saving both time and money. They're designed for fixed installation in a wide range of applications such as museums, board rooms, and auditoriums. Thanks to their 3D capability, they're also perfectly fit for theme park dark rides and interactive experiences.

#### Superior image quality

The F80-Q7 delivers stunning images with highly saturated colors that allow for accurate color reproduction at all times. What's more it features the powerful Barco Pulse processing that allows for sharper images and less latency thanks to its Single Step Processing (SSP).

### Unprecedented business value

With this projector you can increase your uptime while driving costs down. Through its laser-phosphor light source and advanced cooling design, it provides a long operating time without need for lamp changes - resulting in considerable cost-savings on maintenance and consumables.

#### Ultimate installation flexibility

The F80-Q7 gives you more flexibility in projector location and orientation as it can run in any orientation. Thanks to its wide array of all-glass lenses and wide lens shift ranges, the F80-Q7 accommodates almost any projector configuration.



PRODUCT SPECIFICATIONS	F80-Q7
Projector type	Single-chip DLP projector
Technology	0.64" DMD
Resolution	2,560 x 1,600 (WQXGA) native
Input resolutions	4,096 x 2,400 max.
Output Resolutions	2,560 x 1,600 (WQXGA)
Brightness	7,000 lumens
Contrast ratio	1,300:1
Aspect ratio	16:10
Optical lens shift	Motorized zoom, focus, vertical and horizontal shift
Throw Ratio	0.85 - 1.06 ; 1.06 - 1.43 ; 1.43 - 2.12 ; 2.12 - 3.18 and compatible with FLD/FLD+ series (with adapter)
Light source	Laser phosphor
Light source lifetime	Up to 40,000 hours
Orientation	360° rotation, no restrictions
Inputs	HDMI, DVI, HDBaseT, DisplayPort, SDI, DMX
Power requirements	100-240V / 50-60Hz
Power consumption	700 W nominal, 850 W maximum
Noise level (typical at 25°C/77°F)	35 dB(A)
Dimensions (WxLxH)	480 x 680 x 227 mm / 18.9 x 26.7 x 8.9 in
Weight	25.5 kg / 56.2 lbs
Certifications	FCC Class A
Warranty	3 years

### Last updated: 04 Sep 2017

 $Technical\ specifications\ are\ subject\ to\ change\ without\ prior\ notice.\ Please\ check\ www.barco.com\ for\ the\ latest\ information.$ 

