







- True 4K UHD resolution and laser technology -HDR and HLG compatible
- Lights on viewing 3000 lumens of brightness
- Optimised for fast-moving smooth action 16.7ms response time in 4K at 60Hz and 4ms in 1080P at 240Hz
- Flexible and easy installation Four corner correction, 1.3x zoom and vertical lens shift



Get ready for a whole new cinematic experience in the comfort of your own home. The stylish UHZ50 laser projector delivers vivid 4K UHD resolution for incredibly crisp images with exceptional clarity and vibrancy for movies, TV shows, games, and sports. With the included enhanced gaming mode, gamers can enjoy fast-moving action with a 16.7ms response time in 4K at 60Hz and 4ms in 1080P at 240Hz.

Packed with the latest technology and features, this stylish projector boasts HDR and HLG compatibility, three HDMI 2.0 inputs, seamless voice control, streaming apps and a built-in media player. Laser technology provides long-lasting, exceptional colour accuracy with extensive DCI-P3 coverage.

Specifications	
Display/image	
Display technology	
Resolution	UHD (3840x2160)
Brightness	3,000 lumens
Contrast ratio	2,500,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3
Keystone correction - horizontal	+/-40°
Keystone correction - vertical	+/-40°
Has vertical auto keystone	Yes
correction	
Displayable colours (millions)	1073.4
Horizontal scan rate	15.375 ~ 91.146 Khz
Vertical scan rate	50 ~ 120HzHz
Uniformity	80%
Screen size	0.87m ~ 7.68m (34.1" ~ 302.4") diagonal
Lamp info	
Light source type	Laser
LASER life	30,000 hours
Optical	
Throw ratio	1.21:1 ~ 1.59:1
Projection distance (m)	1.2m - 8.1m
Zoom	1.3
Zoom type	Manual
Focal length (mm)	12.81mm~16.74mm
Lens shift	Vertical +10%
Native offset	105%
Lens shift	Yes - {{downloads_link}}
Connectivity Connections	
Connections	Inputs 2 x HDMI 2.0, 3 x USB-A, 1 x HDMI 2.0 (eARC) Outputs 1 x Audio 3.5mm, 1 x S/PDIF Control 1 x PS22, 1 x P.1/5, 1 x 12//tidager, 1 x 2D even
	Control 1 x RS232, 1 x RJ45, 1 x 12V trigger, 1 x 3D sync
General	
Noise level (typical)	27dB
Noise level (max)	29dB
PC compatibility	UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
3D compatibility	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
3D	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian Japanese, Norwegian, Polish, Portuguese, Romanian, Russian Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
24/7 operation	
Operating conditions	0°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85%
Remote control	Backlit home remote
Heat dissipation	918BTU/hour
Speaker count	2
Watts per speaker	10W
In the box	AC power cord
	Remote control inc CR2025 battery Quick start user manual USB wireleas adapter
Input lag	USB wireless adapter 4.00ms
Power	
Power supply	100V ~ 240V, 50-60Hz
Power consumption (standby)	<0.5W
Power consumption (standby)	175W
Power consumption (max)	230W
Weight and dimensions	20077
Dimensions (W x D x H) mm	337 x 265 x 122.5

6.5 kg 4.8 kg

Gross weight

Net weight







Copyright © 2021, Optoma and its logo is a registered trademark of Optoma Corporation. Optoma Europe Ltd is the licensee of the registered trademark. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. All images are for representation purposes only and may be simulated. 18112021061805