Key Features

- 2nd generation laser phosphor technology with up to 30,000 hours lifespan
- 5,000 ANSI Lumens offering bright images in any environment
- Up to 300" ultra large screen with lower cost-per-inch
- Installation flexibility: V lens shift, 1.6x optical zoom, H/V keystone
- Versatile application: 360° projection, portrait mode



Product **Description**

The Luminous Superior series is ViewSonic's lamp-free high brightness lineup for both commercial and educational spaces. The LS751HD adopts industry-leading 2nd generation laser phosphor technology and delivers 5,000 ANSI Lumens while eliminating the use of toxic mercury, reducing the cost and effort of frequent lamp replacement and lowering the total cost of ownership. The lamp-free light source offers enhanced sustainability for a greener environment while delivering up to 300" large images with 1080p high resolution and vivid colors no matter if you're in a boardroom, lecture hall, or public space. The projector boasts high installation flexibility with vertical lens shift, 1.6x optical zoom, easy image adjustment with H/V keystone and 4 corner correction, and diverse applications with 360° projection and portrait mode. The LS751HD also comes with HDMI 2.0b, ensuring access to original 4K quality content with HDR/HLG supported.





1. Front IR 8. RJ45 (LAN Control)
2. Lens 9. RS232
3. HDMI 1.4/HDCP 1.4 10. Zoom Ring
4. HDMI 2.0/HDCP 2.2 11. Focus Ring
5. USB-A (5V/2A, Service) 12. LED Indicator
6. Lens 13. Keypad
7. Audio Out 14. IR

Visit Us www.viewsonic.com

| SPECIFICATION | | OTHERS | |
|---|---|---------------------------------------|---|
| Native Resolution: | 1920x1080 | Power Supply Voltage: | 100-240V+/- 10%, 50/60Hz |
| Brightness: | 5000 (ANSI Lumens) | | (AC in) |
| Contrast Ratio: | 3000000:1 | Power Consumption: | Normal: 245W Standby: <0.5W |
| Display Color: | 1.07 Billion Colors | Operating Temperature: | 0~40°C |
| Light Source Type: | Laser Phosphor | Carton: | Brown |
| Light Source Life (hours) with Normal Mode: | 20000 | Net Weight: | 4.5kg |
| Light Source Life (hours) with SuperEco Mode: | 30000 (Eco) | Gross Weight: Dimensions (WxDxH) with | 6.6kg 337x265x131.5mm |
| Lens: | F=2.5-3.26, f=20.911-32.62mm | Adjustment Foot: | |
| Projection Offset: | 136%+/-5% | Packing Dimensions: | 496x195x387mm |
| Throw Ratio: | 1.4~2.24 | OSD Language: | English, French, German, Spanish, Italian, Portuguese, Dutch, Swedish, Finnish, Greek, Norwegian/Danish, Polish, Russian, Simplified_Chinese, Traditional_Chinese, Korean, Arabic, Japanese, Thai, Hungarian, Czechoslovak, Turkish, Farsi. Vietnamese, Indonesian, Romanian, Slovakian, total 27 languages |
| Optical Zoom: | 1.6X | | |
| Digital Zoom: | 0.8x-2.0x | | |
| Image Size: | 30"-300" | | |
| Throw Distance: | 0.93-14.88m (100"@3.10m) | | |
| Keystone: | H:+/-30° , V:+/-30° | | |
| Lens Shift V. Range: | +0%, -18% | | English, S-Chinese, T- Chinese, Indonesian, Finish, French, German, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, |
| Audible Noise (Normal): | 34dB | | |
| Audible Noise (Eco): | 31dB | User Guide Language: | |
| Input Lag: | 49.9ms | · · · · · · · · · · · · · · · · · · · | Swedish, Turkish, Arabic, Czech, Thai, Vietnamese, total |
| Resolution Support: | VGA(640 x 480) to 4K UHD(3840 x 2160) | STANDARD ACCESSORY | 20 languages |
| HDTV Compatibility: | 480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 4K UHD | Power Cord: | 1 |
| Horizontal Frequency: | 15K-102KHz | Remote Control: | 1 |
| Vertical Scan Rate: | 23-120Hz | QSG: | Yes |
| INPUT | | Warranty Card: | Yes (CN Only) |
| HDMI: | 2 (HDMI 2.0/ HDCP 2.2 HDMI 1.4/ HDCP 1.4) | OPTIONAL ACCESSORY | |
| | | Wall/Ceiling Mount: | PJ-WMK-007 |
| ОИТРИТ | | | |
| Audio-out (3.5mm): | 1 | | |
| Speaker: | 15W x2 | | |
| USB Type A (Power): | 1 (5V/1.5A) | | |
| CONTROL | | | |
| RS232 (DB 9-pin male): | 1 | | |
| RJ45 (LAN control): | 1 | | |
| USB Type A (Services): | 1 (share with USB A Output) | | |